



Jellemzők

Twin KPL légfüggöny

- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Önálló ház horganyzott acéllemezbe, szerkezeti epoxi-poliészter festéssel, alapkitételben RAL9016 fehér színben. Megrendelésre kérhető egyéb színekben vagy rozsdamentes acélból.
- Széles bemeneti rács csiszolt élekkel, mely nem igényel komoly karbantartást.
- Eloxált alumínium kimeneti lapátok szárnykialakítással, mindkét oldalon 0 és 15° között állítható.
- Kettős bemeneti centrifugális ventilátorok, külső rotor motorral és alacsony zajszinttel. 5 sebességfokozat. Az EC modellek rendkívül alacsony fogyasztású hatékony ventilátorokkal szerelve.
- „A” típus fűtés nélkül, kizárólag levegővel.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

Műszaki adatok

50Hz

Fűtetlen		
modell	(m ² /h)	(m)
TWIN KPL M 1500 A	9,8-13,1	
TWIN KPL M 2000 A	9,8-13,1	
TWIN KPL M 2500 A	9,8-13,1	
TWIN KPL M 3000 A	9,8-13,1	
TWIN KPL ECM 1500 A	9,8-13,8	
TWIN KPL ECM 2000 A	9,8-13,8	
TWIN KPL ECM 2500 A	9,8-13,8	
TWIN KPL ECM 3000 A	9,8-13,8	
TWIN KPL G 1500 A	9,8-13,1	
TWIN KPL G 2000 A	9,8-13,1	
TWIN KPL G 2500 A	9,8-13,1	
TWIN KPL G 3000 A	9,8-13,1	
TWIN KPL ECG 1500 A	9,8-13,8	
TWIN KPL ECG 2000 A	9,8-13,8	
TWIN KPL ECG 2500 A	9,8-13,8	
TWIN KPL ECG 3000 A	9,8-13,8	

60Hz

Fűtetlen



modell	(m³/h)	(m)
TWIN KPL ECM 1500 A	9,8-13,8	
TWIN KPL ECM 2000 A	9,8-13,8	
TWIN KPL ECM 2500 A	9,8-13,8	
TWIN KPL ECM 3000 A	9,8-13,8	
TWIN KPL ECG 1500 A	9,8-13,8	
TWIN KPL ECG 2000 A	9,8-13,8	
TWIN KPL ECG 2500 A	9,8-13,8	
TWIN KPL ECG 3000 A	9,8-13,8	

Méreték

Twin KPL légfüggönyök méretei